



M8 Series

- M8 female assembly connector ,straight.
- Description:M8 female straight metal shielded screw assembly connector ,A/B/D coded.



Assembly Instruction



1. Bead parts.
2. Strip cable, shorten shielding braid and revert to shielding ring.
3. Connect single wires.
4. Screw housing to either male or female contact carrier and tighten pressing screw.

Technical Data

Pin No.	3	4	4	5	6	8
Coding	A	A	D	B	A	A
Pin for reference						
Type	Assembly					
Rated current	3A	3A	4A	3A	1.5A	1.5A
Rated voltage	60V	60V	60V	30V	30V	30V
Operating Temperature	-25℃~85℃					
Degree of protection	IP67/IP68					
Connector locking system	Screw					
Mechanical operation	>500 mating cycles					
Contact resistance	≤10mΩ					
Material of connector	CuZn,TPU					
Contact plating	Au(gold plating)					
Outlet	Suitable OD 4-8mm cable					

Order Information

Part No.	Model No.
M8- <input type="text"/> -FS- <input type="text"/> -SH	RG082011
<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> Coded <input type="text"/> Coded </div> <div style="text-align: center;"> Pin No. <input type="text"/> Pin No. </div> </div>	

Remark:Contact us any time if you have custom requirements.